

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)

PCT

(10) International Publication Number
WO 03/060289 A1

(51) International Patent Classification⁷: **E21B 43/10**,
29/10, 33/10

(21) International Application Number: PCT/GB02/05933

(22) International Filing Date:
27 December 2002 (27.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0131019.2 27 December 2001 (27.12.2001) GB

(71) Applicant (for all designated States except US): **WEATHERFORD/LAMB, INC.** [US/US]; Suite 600, 515 Post Oak Boulevard, Houston, TX 77027 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **DUGGAN, Andrew, Michael** [GB/GB]; 43 Argyll Place, Aberdeen AB25 2HU (GB). **INNES, Gareth** [GB/GB]; C/O Weatherford Completion Systems, Norfolk House, Pitmedden Road, Dyce, Aberdeen AB21 0DP (GB).

(74) Agent: **MACDOUGALL, Donald, Carmichael**; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: BORE ISOLATION



(57) Abstract: A method of isolating a section of a drilled bore (10) containing a problem zone (12) comprises: providing a section of tubing (16); locating the tubing in the section of the bore; and expanding the tubing and forming at least an outer portion (20) of the tubing to conform to irregularities in the bore wall, to isolate the problem zone. The tubing may feature a formable outer section (20), and the expansion of the tubing may be achieved using a compliant rotary expander.



WO 03/060289 A1



(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

BORE ISOLATION

FIELD OF THE INVENTION

This invention relates to bore isolation, and in particular to methods and apparatus for use in isolating a section of a drilled bore, or sealing the wall of a section of a drilled bore.

5 BACKGROUND OF THE INVENTION

In the oil and gas exploration and production industry, wells are created by drilling bores from surface to access subsurface hydrocarbon reservoirs. A drill bit is mounted on the end of a string of drill pipe which extends from the surface. The string and bit may be rotated from surface, or the bit may be rotated by a downhole motor. Drilling fluid or "mud" is pumped through the drill string from the surface, to exit the string at the bit. The fluid carries the cuttings produced by the drill bit to surface, through the annulus between the drill string and the bore wall.

The drilled "open" bore is lined with metallic tubing, known as casing or liner, which is secured and sealed in the bore by injecting a cement slurry into the annulus between the liner and the bore wall.

Often, a drilling operation will encounter a "loss

zone", typically a void or an area of porous or fractured strata or a formation in which the in situ pressure regime is lower than in the other exposed zones. When drilling through a loss zone, large volumes of drilling fluid may be lost, at great expense and inconvenience. The loss of drilling fluid may also result in a significant differential fluid pressure between the drill string and the annulus, during drilling and indeed any other downhole operation, which has significant implications for operational safety and operation of conventional downhole tools and devices.

Furthermore, some production zones, such as fractured carbonate reservoirs, act as loss zones. Thus, following completion of a bore, and before oil is produced, much of the drilling fluid lost into the reservoir during drilling must be removed, by "back-producing", which is both time consuming and expensive.

A further difficulty when a drilled bore crosses a loss zone is that it is difficult to place and successfully cement a conventional bore liner across the zone; the loss zone prevents the cement from being placed across the liner.

As noted above, fractured carbonate reservoirs which are one of the producing formations for oil can act as multiple loss zones. However, to obtain increased production rates, it is desirable that a well accesses a

large area of reservoir and thus may intersect many loss zones. Thus, if the first fracture encountered cannot be isolated, by lining and cementing, due to losses, the well cannot be drilled further, and the well can only be produced from this first fracture, limiting production.

A different but related problem is encountered when a drilled bore intersects a relatively high pressure, or "over pressured" zone, which may result in undesirable and possibly uncontrolled flow of fluid into a bore.

This flow of fluid into the bore disrupts the normal circulation of drilling fluid, and may have well control implications as the density of the fluid column changes. Furthermore, the reliance on increasing the drilling fluid pressure to retain fluid in the over pressured zone by, for example, using relatively dense drilling fluid, limits the ability to drill the bore beyond the over pressured zone, since fluid losses may occur into other exposed zones which are naturally of a normal or sub-normal pressure regime.

It is among the objectives of embodiments of the present invention to obviate or mitigate these difficulties.

SUMMARY OF THE INVENTION

According to a first aspect of the present invention, there is provided a method of isolating a

section of a drilled bore, the method comprising the steps of:

providing a section of tubing;

locating the tubing in a section of a bore;

5 expanding the tubing by moulding at least an outer portion of the tubing to conform to irregularities in the bore wall, to isolate at least a portion of the bore wall.

A second aspect of the invention relates to
10 apparatus for use in implementing the method.

The invention has particular application in isolating problem zones, such as loss zones, over pressured zones, water-producing zones, or a section of bore where a mechanical collapse has occurred or is
15 considered likely to occur, and thus the section of tubing will typically be located in a section of bore across such a problem zone.

Preferably, the tubing wall comprises a structural layer and an outer relatively formable layer for contact
20 with the bore wall; the outer layer may be deformed on contact with the bore wall to provide a contact area which follows the irregularities of the bore wall, and preferably to provide a hydraulic seal between the tubing and the bore wall. Typically, the structural layer will
25 be metallic, such as a steel or other alloy, but may be of any appropriate material. Typically, the formable

layer will be of an elastomer, but may also be a relatively soft metal or other malleable material. In certain embodiments, the outer layer may be formed of a material which swells or expands in situ. Such swelling or expansion may be temperature dependent, and take advantage of the elevated temperatures normally experienced downhole, or may be in response to the presence of a reactant or catalyst, or an energy input. In one embodiment, a swelling elastomer may be utilised, which swells through contact with hydrocarbon fluids.

Preferably, the tubing is expanded beyond its yield point, such that the expansion of the tubing is retained by the tubing itself. In other embodiments, the tubing may not reach yield during expansion and may be provided with some other means or mechanism for retaining the desired expanded form.

Preferably, the tubing is located in a bore below an existing section of bore-lining tubing. An upper end of the expanded tubing overlaps the existing tubing, and is most preferably sealed thereto. However, in other embodiments the tubing may be located solely within an open portion of the bore, and does not overlap with any existing tubing.

Preferably, the method further comprises drilling below an existing section of bore-lining tubing to a larger diameter than the inner diameter of the existing

tubing. This may be achieved by, for example, use of an expandable or bicentred bit, or by means of an underreamer. This allows tubing placed below the existing tubing to be expanded to a diameter similar to or larger than that of the existing tubing, such that there is no significant loss in bore diameter.

Preferably, the method further comprises drilling a lower portion of the section of bore to a larger diameter than an upper section of the bore, and expanding a lower portion of the tubing to a larger expanded diameter than an upper section of the tubing. This larger diameter portion may then be utilised to accommodate the upper end of a further tubing section, such that a further tubing section may be installed without loss of hole size.

Preferably, the tubing is expanded using a variable diameter expansion device, that is a device which is capable of expanding the tubing to a variety of different diameters, and thus accommodate irregularities in the bore wall and maintain the expanded tubing in contact with a large area of the tubing wall. Most preferably, a compliant rotary or rolling expander is utilised, that is an expander which comprises at least one expansion member, and typically a plurality of expansion members, which operate independently and are biased radially outwardly to engage and expand the tubing as the expander is rotated or otherwise translated through the tubing.

Such an expander is described in our earlier application W000/37766, the disclosure of which is incorporated herein by reference. Alternatively, an axially translatable compliant expander may be utilised, such as
5 sold by the applicant under the ACE trade mark, and examples of which are described in our application GB 0128667.3, the disclosure of which is incorporated herein by reference. The use of such expanders in open hole applications offers numerous advantages over conventional
10 cone or swage expansion devices, with which it is not possible to obtain full circumferential contact with the surrounding bore wall, and thus not possible to achieve sealing contact with the bore wall.

In other embodiments, a fixed diameter expansion
15 device, such as a cone or mandrel, may be utilised to expand the tubing, in such a case the moulding of the outer surface of the tubing to the bore wall may be achieved by provision of a formable outer portion on the tubing, or an outer portion which swells or otherwise
20 expands in situ.

In certain embodiments two or more expansion devices may be provided, and the expansion devices may differ, for example a fixed diameter expansion device may be utilised in combination with a compliant expansion
25 device.

In other embodiments, cement may be injected into

the annulus between the tubing and the bore wall.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figures 1 and 2 are schematic representations of steps in the process of isolating a problem zone, in accordance with a preferred embodiment of the present invention.

10 DETAILED DESCRIPTION OF THE DRAWINGS

Reference is made to Figures 1 and 2 of the drawings, which illustrate, somewhat schematically, a method of isolating a problem formation in accordance with a preferred embodiment of the present invention. A bore 10 has been drilled through a formation or zone 12, which may take the form of a loss zone, over pressured zone, water producing zone, or a mechanically unstable zone. The zone is located beyond the lower end of a previously installed and cemented casing 14. Modern surveying techniques are such that the presence of the zone will likely have been predicted, such that the operator will be equipped and prepared to deal with the problem zone, as described below.

In this example the operator has been drilling the

bore beyond the casing 14 to a diameter corresponding to the inner diameter of the casing. However, in the vicinity of the problem zone 12, the bore is drilled to a larger diameter, for example by means of a bi-centre bit, to a diameter closer to the outer diameter of the casing 14. Furthermore, for a section beyond the problem zone 12, the bore has been drilled to a still larger diameter. It should also be noted that the lower portion of the annulus between the casing 14 and the bore wall is substantially free of cement, as may be achieved using the apparatus and methods disclosed in applicant's PCT/GB01/04202 and co-pending US patent application, the disclosures of which are incorporated herein by reference.

A section of tubing, in the form of a patch 16, is then run into the bore 10, and positioned across the problem zone 12, as shown in Figure 1, the upper end of the patch 16 overlapping the lower end of the casing 14. The patch 16 features an inner structural steel layer 18, and an outer formable elastomer layer 20. The patch 16 is run into the bore on a running string provided with a compliant rotary expander 22, which features a number of radially movable piston-mounted rollers 24.

By supplying hydraulic fluid at elevated pressure to the interior of the expander 22, the rollers 24 are radially extended to contact the inner surface of the

patch. The actuated expander 22 is then rotated within the patch 16, which causes the patch 16 to expand into contact with the inner face of the casing 14 and then expand the casing 14, such that the inner diameter of the patch 16 may be expanded to a similar diameter to the unexpanded casing 14. The expander then continues through the patch 16, expanding the remainder of the patch into intimate contact with the bore wall. The degree of expansion provided by the expander is selected to be sufficient to urge the outer face of the patch 16 into the inner wall of the casing, and then the bore wall, with some degree of force, such that the outer elastomer layer 20 forms a seal with the casing 14 and is deformed and is moulded to conform to the irregular bore wall. Furthermore, as a compliant expander 22 is being utilised, any substantial variations in bore wall profile may be accommodated by expanding the structural layer 20 to different extents.

The expander 22 continues its progress through the patch 16, such that the expanded patch follows the profile of the bore wall, forms a hydraulic seal with the bore wall, and isolates the problem zone.

The provision of the "oversize" bore in the vicinity of the problem zone allows expansion of the patch 16 to a diameter corresponding up to and beyond the diameter of the unexpanded casing 14, such that the presence of the

patch 16 does not result in a loss of bore diameter.

Furthermore, if a further patch is required (shown in chain-dotted outline), this may be run into the bore to overlap with the existing patch within the lower over-expanded portion of the patch 16, such that there is no loss of bore diameter experienced at the overlap.

It will thus be apparent to those of skill in the art that this embodiment of the present invention provides an effective and convenient means for isolating problem formations in a well, without requiring use of cement or other curable fluids.

It will further be apparent to those of skill in the art that the embodiment described above is merely exemplary of the present invention, and that various modifications and improvements may be made thereto without departing from the scope of the invention. For example, in another embodiment, the patch may be located in a section of open hole, spaced from any existing casing. In such a case, it is preferable that the bore is enlarged to accommodate the patch such that patched bore wall has a substantially constant diameter despite the presence of the expanded patch. In the example described, the tubing is solid-walled throughout its depth; in other embodiments, it may be possible to provide a tubing having at least a structural element of slotted or perforated tubing.

CLAIMS

1. A method of isolating a section of a drilled bore,
the method comprising the steps of:

providing a section of tubing;

5 locating the tubing in a section of a bore;

expanding the tubing and to isolate at least a
portion of the bore wall.

2. The method of claim 1, comprising forming at least
an outer portion of the tubing to conform to
10 irregularities in the bore wall.

3. The method of claim 1 or 2, comprising locating the
section of tubing across a problem zone, and isolating
the problem zone from the bore with the expanded tubing.

4. The method of claim 3, wherein the problem zone is a
15 loss zone.

5. The method of claim 3, wherein the problem zone is
an over pressured zone.

6. The method of claim 3, wherein the problem zone is a

water-producing zone.

7. The method of claim 3, wherein the problem zone is a section of bore where a mechanical collapse has occurred or is considered likely to occur.

5 8. The method of any of the preceding claims, comprising the steps of:

providing a tubing section having a tubing wall comprising a structural layer and an outer relatively formable layer; and

10 expanding the tubing such that the outer relatively formable layer contacts the bore wall and is deformed on contact with the bore wall to provide a contact area which follows the irregularities of the bore wall.

15 9. The method of claim 8, wherein the outer relatively formable layer swells to ensure contact with the bore wall.

10. The method of any of the preceding claims, comprising expanding the tubing to provide a hydraulic seal between the tubing and the bore wall.

20 11. The method of any of the preceding claims, comprising expanding the tubing beyond its yield point.

12. The method of any of the preceding claims,
comprising locating the tubing in a bore below an
existing section of bore-lining tubing.

5 13. The method of claim 12, comprising locating the
section of tubing such that an upper end of the expanded
tubing overlaps the existing tubing.

14. The method of claim 13, comprising expanding the
upper end of the section of tubing to form a seal with
the existing tubing.

10 15. The method of any of claims 1 to 12, comprising
locating the tubing within an open or unlined portion of
the bore, spaced from existing tubing.

16. The method of any of the preceding claims, further
comprising drilling a section of bore below an existing
15 section of bore-lining tubing to a larger diameter than
the inner diameter of the existing tubing and expanding
the section of tubing placed below the existing tubing to
a diameter similar to that of the existing tubing.

20 17. The method of claim 16, further comprising drilling
a lower portion of said section of bore to a larger
diameter than an upper section of the bore, and expanding

a lower portion of the section of tubing to a larger expanded diameter than an upper section of the tubing.

18. The method of claim 17, further comprising locating an upper end of a further tubing section in said larger diameter lower portion, and expanding said further tubing section.

19. The method of any of the preceding claims, comprising expanding the tubing using a variable diameter expansion device.

20. The method of any of the preceding claims, comprising expanding the section of tubing using a compliant rotary expansion device.

21. The method of any of the preceding claims, comprising expanding the section of tubing using a compliant axial expansion device.

22. The method of any of the preceding claims, comprising expanding the section of tubing using a fixed diameter expansion device.

23. The method of any of the preceding claims, comprising injecting a cement slurry into an annulus

between the section of tubing and the bore wall.

24. The method of any of the preceding claims, comprising locating at least a portion of the tubing in an unlined section of the drilled bore.

5 25. The method of any of the preceding claims, comprising locating substantially all of the tubing in an unlined section of the drilled bore.

10 26. The method of any of claims 1 to 24, comprising locating at least a portion of the tubing in a lined section of the drilled bore.

27. The method of claim 26, comprising locating substantially all of the tubing in a lined section of the drilled bore.

15 28. A method of isolating a section of a drilled bore, the method comprising the steps of:

providing a section of tubing;

locating at least a portion of the tubing in an unlined section of a drilled bore;

20 expanding the tubing and to isolate at least a portion of the bore wall.

29. The method of claim 28, comprising forming at least an outer portion of the tubing to conform to irregularities in the unlined section of bore wall.

30. The method of claim 28 or 29, comprising expanding
5 the tubing into contact with the unlined section of bore wall.

31. Apparatus for use in isolating a problem zone in a bore, the apparatus comprising a section of expandable tubing and an expansion device, whereby the expansion
10 device is operable to expand the tubing into contact with a section of surrounding bore wall.

32. The apparatus of claim 31, wherein at least a portion of the tubing is adapted to conform to a section of unlined bore wall.

15 33. The apparatus of claim 31 or 32, wherein at least a portion of the tubing is adapted to conform to a section of lined bore wall.

34. The apparatus of claim 31, wherein the tubing is adapted to conform to both a section of unlined bore wall
20 and a section of lined bore wall.

35. The apparatus of any of claims 31 to 34, wherein the tubing has a compliant outer portion.

36. The apparatus of any of claims 31 to 35, wherein the tubing wall comprises a structural layer and an outer
5 relatively formable layer for contact with the bore wall.

37. The apparatus of claim 36, wherein the formable layer is of an elastomer.

38. The apparatus of claim 36 or 37, wherein the outer layer is of a material adapted to swell in situ.

10 39. The apparatus of any of claims 31 to 38, wherein the tubing is selected such that, on expansion, the tubing wall will pass through yield.

40. The apparatus of any of claims 31 to 39, wherein the expansion device comprises a variable diameter expansion
15 tool.

41. The apparatus of any of the claims 31 to 40, wherein the expansion device comprises a compliant rotary expander.

42. The apparatus of any of claims 31 to 41, wherein the

expansion device comprises a compliant axial expansion device.

43. The apparatus of any of claims 31 to 42, wherein the expansion device comprises a fixed diameter expansion tool.

1/2




Fig.1




Fig.2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/05933

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B43/10 E21B29/10 E21B33/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2 812 025 A (DOHERTY WILFRED T ET AL) 5 November 1957 (1957-11-05) column 1, line 66 -column 2, line 3; figure 7 column 5, line 69 -column 6, line 6	1-7, 10-12, 15,24, 25, 28-32,39
Y	---	8,35-37
X	US 5 348 095 A (WORRALL ROBERT N ET AL) 20 September 1994 (1994-09-20) column 2, line 5 - line 8; figure 7 --- -/--	1,2, 10-12, 22,25, 28-32, 39,43



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

16 May 2003

Date of mailing of the international search report

23/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk

Authorized officer

INTERNATIONAL SEARCH REPORT

Inte: ional Application No

PCT/GB 02/05933

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 976 322 A (ABDRAKHMANTOV GABRASHIT S ET AL) 11 December 1990 (1990-12-11) column 1, line 11 - line 19; figures 2,3 column 2, line 20 - line 36 column 3, line 33 - line 47	1-7, 10-12, 15,16, 22,24, 25, 28-32, 39,43
X	WO 99 35368 A (SHELL CANADA LTD ;SHELL INT RESEARCH (NL)) 15 July 1999 (1999-07-15) page 6, line 2 -page 7, line 23; figure 1	1,2, 10-14, 22-26, 28-34, 39,43
Y	---	27
Y	WO 99 02818 A (METCALFE PAUL DAVID ;PETROLINE WELLSYSTEMS LTD (GB)) 21 January 1999 (1999-01-21) page 5, line 11 -page 6, line 17; figures 1,2	8,35-37
Y	---	
Y	WO 01 33037 A (STEWART R BRUCE ;COOK ROBERT LANCE (US); COWAN KENNETH MICHAEL (US) 10 May 2001 (2001-05-10) page 14, line 28 -page 15, line 13; figure 3C	27
A	---	
A	WO 00 37766 A (ASTEC DEV LTD ;SIMPSON NEIL ANDREW ABERCROMBI (GB)) 29 June 2000 (2000-06-29) cited in the application See abstract figure 1	1,28,31

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/05933

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2812025	A	05-11-1957	NONE	
US 5348095	A	20-09-1994	AU 670948 B2 AU 4324493 A CA 2137560 A1 DE 69306110 D1 DE 69306110 T2 DK 643794 T3 WO 9325799 A1 EP 0643794 A1 JP 7507610 T NO 944721 A NZ 253124 A OA 10117 A RU 2103482 C1 SG 46560 A1	08-08-1996 04-01-1994 23-12-1993 02-01-1997 05-06-1997 05-05-1997 23-12-1993 22-03-1995 24-08-1995 07-12-1994 27-02-1996 18-12-1996 27-01-1998 20-02-1998
US 4976322	A	11-12-1990	SU 1679030 A1 AU 606777 B2 AU 2939589 A CA 1301635 A1 CN 1034973 A ,B DE 3855787 D1 EP 0353309 A1 HU 57371 A2 IN 170723 A1 JP 2530737 B2 JP 2503097 T MX 171802 B NO 893732 A WO 8906739 A1	23-09-1991 14-02-1991 11-08-1989 26-05-1992 23-08-1989 20-03-1997 07-02-1990 28-11-1991 09-05-1992 04-09-1996 27-09-1990 15-11-1993 19-09-1989 27-07-1989
WO 9935368	A	15-07-1999	AU 740213 B2 AU 2418699 A BR 9814563 A CA 2316978 A1 DE 69808139 D1 DK 1044316 T3 EA 2563 B1 WO 9935368 A1 EP 1044316 A1 JP 2002500306 T NO 20003402 A NZ 505059 A	01-11-2001 26-07-1999 17-10-2000 15-07-1999 24-10-2002 04-11-2002 27-06-2002 15-07-1999 18-10-2000 08-01-2002 25-08-2000 28-03-2003
WO 9902818	A	21-01-1999	AU 8348898 A GB 2347446 A ,B WO 9902818 A1 US 6457533 B1	08-02-1999 06-09-2000 21-01-1999 01-10-2002
WO 0133037	A	10-05-2001	AU 1356601 A CA 2389094 A1 GB 2374622 A NO 20022048 A WO 0133037 A1	14-05-2001 10-05-2001 23-10-2002 28-06-2002 10-05-2001
WO 0037766	A	29-06-2000	AU 1867900 A	12-07-2000

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/05933

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0037766 A		AU 1868800 A	12-07-2000
		AU 1868900 A	12-07-2000
		AU 1876600 A	12-07-2000
		AU 1876800 A	12-07-2000
		CA 2356130 A1	29-06-2000
		CA 2356131 A1	29-06-2000
		CA 2356144 A1	29-06-2000
		CA 2356148 A1	29-06-2000
		CA 2356184 A1	29-06-2000
		CA 2356194 A1	29-06-2000
		EP 1147287 A2	24-10-2001
		EP 1141517 A1	10-10-2001
		EP 1141515 A1	10-10-2001
		EP 1144802 A2	17-10-2001
		EP 1151180 A1	07-11-2001
		EP 1141518 A1	10-10-2001
		WO 0037766 A2	29-06-2000
		WO 0037771 A1	29-06-2000
		WO 0037768 A1	29-06-2000
		WO 0037767 A2	29-06-2000
		WO 0037772 A1	29-06-2000
		WO 0037773 A1	29-06-2000
		GB 2345308 A	05-07-2000
		GB 2346632 A	16-08-2000
		GB 2346400 A	09-08-2000
		GB 2346909 A	23-08-2000
		GB 2347445 A	06-09-2000
		NO 20012596 A	27-07-2001
		NO 20012597 A	27-07-2001
		NO 20012598 A	30-07-2001
		NO 20012599 A	30-07-2001
		NO 20012600 A	30-07-2001
		NO 20012865 A	07-08-2001
		US 2002195256 A1	26-12-2002
		US 2003019638 A1	30-01-2003
		US 2002166668 A1	14-11-2002
		US 6543552 B1	08-04-2003
		US 2002145281 A1	10-10-2002
		US 2002079106 A1	27-06-2002
		US 2002060079 A1	23-05-2002
		US 2002112338 A1	22-08-2002